V4 2.5-10x56 NFX



Gen3 | MRAD | A4N

Référence :442511139

- based on Gen. 3 - special version FX

- FX = More field of view & better insight

- Field of view 15m-3.7m

- less marginal area in view

- Reticle adjustment metal towers (no plastic)

- CT (clear transmission) glass (low dispersion)

- double scaling (double turn)

- Zero stop for ASV (zero stop)

- hard, tactical 0.1 MRAD click detent (1 cm/click)

- Adjustment range 184 clicks = 1.8 m at 100 m

- new design of magnification adjustment ring

- new reticle 4 (A4N) with significantly finer bars

- Accessories: 1x flip caps, cleaning cloth, DDoptics chip, targets, scopes instructions, ballistics set

Hunt to the last light of the rifle

The N-FX V4 2.5-10x56 is a rifle scope that specifically meets the requirements of night hunting. The field of view of 15 m and the good view ensure perfect conditions for quick shots, such as on a drive hunt. The 10x magnification enables a reliable addressing until the last daylight. Even long-distance shots of up to 800 m have already been completed with this scope.

The extra complex HD optics offers a high-contrast and color-true image with outstanding edge sharpness properties due to the coating specially developed for this optics, which does not allow any reflections or scattered light, even with 10x magnification. In particular, color fringes have been reduced to a minimum. Light

©ProDigiT 2002-2026

transmission values between 92-94% ensure excellent performance at night and twilight.

Hunting A4N illuminated reticle with intelligent IFiber illuminated dot

The V4 2.5-10x56 N-FX rifle scope has the successful, modern 4N reticle.

New features

What's new about the latest generation rifle scopes?

At first glance, 3 changes immediately catch the eye:

1. The magnification adjustment ring has been noticeably changed and now provides more grip thanks to its coarser structure.

2. Reticle 4 has become significantly finer and creates more space in the middle.

3. The reticle adjustment is made of metal, is more clearly defined and has double turn and zero stop.

Adjustment range of the reticle adjustment

The rifle scope has a tactical 0.1 MRAD adjustment. For users in Europe, this means simple application in the decimal system.

Total travel: 21 MRAD

Adjustment range / click at 100m: 1cm

Adjustment range / click at 200m: 2cm

Adjustment range / click at 300m: 3cm

Adjustment range / click at 900m: 9cm

©ProDigiT 2002-2026